

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLMA 1025-75	1 ... 2.5 GHz	75 / 90	48.8 / 51 ±2	15 / 20	800	3 HU, 630 mm	22
BLMA 1025-150	1 ... 2.5 GHz	150 / 180	51.8 / 54 ±2	20 / 20	1100	3 HU, 630 mm	25
BLMA 1025-200	1 ... 2.5 GHz	200 / 250	53 / 55 ±2	15 / 20	1400	4 HU, 630 mm	32
BLMA 1025-250	1 ... 2.5 GHz	250 / 350	54 / 56 ±2	20 / 20	2000	4 HU, 630 mm	36
BLMA 1025-300	1 ... 2.5 GHz	300 / 350	54.8 / 57 ±2	15 / 20	2200	4 HU, 630 mm	37
BLMA 1025-500	1 ... 2.5 GHz	500 / 550	57 / 59 ±2	18 / 20	3500	8 HU, 630 mm	88
BLMA 1025-1000	1 ... 2.5 GHz	1000 / 1100	60 / 62 ±2	20 / 20	9000	12 HU, 800 mm	160
BLMA 1025-1500	1 ... 2.5 GHz	1500 / 1600	61.8 / 64 ±2	15 / 20	14000	17 HU, 630 mm	210
BLMA 1025-2000	1 ... 2.5 GHz	2000 / 2100	63 / 65 ±2	15 / 20	18000	24 HU, 800 mm	230

For individual data sheets, please click on the above model name

1 HU = 44.45 mm