

**STANDARD MODELS**

| Model           | Frequency Range | Output Power<br>$P_N$ min / typ<br>W | Gain<br>min / typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|-----------------|-----------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BLWA 0211-100   | 20 ... 110 MHz  | 100 / 120                            | 50 / 52 ±2              | 20 / 15                       | 450              | 3 HU, 630 mm                       | 20           |
| BLWA 0211-200   | 20 ... 110 MHz  | 200 / 250                            | 53 / 55 ±2              | 20 / 15                       | 800              | 3 HU, 630 mm                       | 30           |
| BLWA 0211-500   | 20 ... 110 MHz  | 500 / 600                            | 57 / 59 ±2              | 20 / 15                       | 1800             | 4 HU, 630 mm                       | 35           |
| BLWA 0211-1000  | 20 ... 110 MHz  | 1000 / 1100                          | 60 / 62 ±2              | 20 / 12                       | 3000             | 5 HU, 630 mm                       | 46           |
| BLWA 0211-1250  | 20 ... 110 MHz  | 1250 / 1400                          | 61 / 63 ±2              | 20 / 15                       | 5000             | 9 HU, 630 mm                       | 100          |
| BLWA 0211-1800  | 20 ... 110 MHz  | 1800 / 2000                          | 62.5 / 65 ±2            | 20 / 15                       | 7500             | 11 HU, 630 mm                      | 135          |
| BLWA 0211-2500  | 20 ... 110 MHz  | 2500 / 2700                          | 64 / 66 ±2              | 20 / 15                       | 9800             | 12 HU, 800 mm                      | 175          |
| BLWA 0211-3000  | 20 ... 110 MHz  | 3000 / 3300                          | 64.8 / 67 ±2            | 20 / 15                       | 20000            | 18 HU, 800 mm                      | 300          |
| BLWA 0211-4000  | 20 ... 110 MHz  | 4000 / 4500                          | 66 / 68 ±2              | 20 / 15                       | 23000            | 24 HU, 800 mm                      | 400          |
| BLWA 0211-5000  | 20 ... 110 MHz  | 5000 / 5500                          | 67 / 69 ±2              | 20 / 15                       | 30000            | 37 HU, 800 mm                      | 460          |
| BLWA 0211-7000  | 20 ... 110 MHz  | 7000 / 8000                          | 68.4 / 71 ±2            | 20 / 15                       | 35000            | 2x 37 HU, 800 mm                   | 590          |
| BLWA 0211-10000 | 20 ... 110 MHz  | 10000 / 11000                        | 70 / 72 ±2              | 20 / 12                       | 60000            | 2x 37 HU, 800 mm                   | 1000         |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm