

STANDARD MODELS

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|-------------------|--------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 0101-5 | 9 kHz ... 1000 MHz | 5 / 8 | 37 / 39 ±2 | 20 / 20 | 150 | 2 HU, 430 mm | 11 |
| BSA 0101-7.5 | 9 kHz ... 1000 MHz | 7.5 / 10 | 38.8 / 41 ±2 | 20 / 20 | 230 | 2 HU, 430 mm | 11 |
| BSA 0101-10 | 9 kHz ... 1000 MHz | 10 / 11 | 40 / 42 ±2 | 20 / 20 | 250 | 2 HU, 430 mm | 11 |
| BSA 0101-25/30D | 9 kHz ... 1000 MHz | | | | 350 | 2 HU, 430 mm | 15 |
| | 9 kHz ... 250 MHz | 25 / 30 | 44 / 46 ±2 | 20 / 20 | | | |
| | 200 ... 1000 MHz | 30 / 35 | 44.8 / 47 ±2 | 20 / 20 | | | |
| BSA 0101-75/60D | 9 kHz ... 1000 MHz | | | | 450 | 3 HU, 630 mm | 23 |
| | 9 kHz ... 400 MHz | 75 / 100 | 48.8 / 51 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 60 / 75 | 47.8 / 50 ±2 | 20 / 20 | | | |
| BSA 0101-100D | 9 kHz ... 1000 MHz | | | | 620 | 3 HU, 630 mm | 24 |
| | 9 kHz ... 400 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |
| BSA 0101-150/100D | 9 kHz ... 1000 MHz | | | | 700 | 3 HU, 630 mm | 25 |
| | 9 kHz ... 400 MHz | 150 / 180 | 51.8 / 54 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |
| BSA 0101-150D | 9 kHz ... 1000 MHz | | | | 1250 | 4 HU, 630 mm | 30 |
| | 9 kHz ... 100 MHz | 150 / 175 | 51.8 / 54 ±2 | 20 / 20 | | | |
| | 80 ... 1000 MHz | 150 / 160 | 51.8 / 54 ±2 | 20 / 20 | | | |
| BSA 0101-200D | 9 kHz ... 1000 MHz | | | | 1750 | 4 HU, 630 mm | 35 |
| | 9 kHz ... 400 MHz | 200 / 250 | 53 / 55 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 200 / 230 | 53 / 55 ±2 | 20 / 20 | | | |
| BSA 0101-250/100D | 9 kHz ... 1000 MHz | | | | 1100 | 4 HU, 630 mm | 41 |
| | 9 kHz ... 400 MHz | 250 / 280 | 54 / 56 ±2 | 20 / 18 | | | |
| | 400 ... 1000 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 20 | | | |
| BSA 0101-250D | 9 kHz ... 1000 MHz | | | | 2050 | 4 HU, 630 mm | 47 |
| | 9 kHz ... 400 MHz | 250 / 300 | 54 / 56 ±2 | 20 / 20 | | | |
| | 400 ... 1000 MHz | 250 / 300 | 54 / 56 ±2 | 20 / 20 | | | |
| BSA 0101-500D | 9 kHz ... 1000 MHz | | | | 4000 | 6 HU, 630 mm | 62 |
| | 9 kHz ... 250 MHz | 500 / 600 | 57 / 59 ±2 | 20 / 18 | | | |
| | 200 ... 1000 MHz | 500 / 600 | 57 / 59 ±2 | 20 / 20 | | | |

BSA 9 kHz ... 1000 MHz Solid State Amplifiers

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|----------------|--------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 0101-1000D | 9 kHz ... 1000 MHz | | | | 9000 | 37 HU, 800 mm | 300 |
| | 9 kHz ... 100 MHz | 1000 / 1200 | 60 / 62 ±2 | 20 / 18 | | | |
| | 100 ... 1000 MHz | 1000 / 1200 | 60 / 62 ±2 | 20 / 20 | | | |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm