

STANDARD MODELS

| Model          | Frequency Range   | Output Power<br>$P_N$ min / typ<br>W | Gain<br>min / typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|----------------|-------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 0110-100   | 9 kHz ... 100 MHz | 100 / 125                            | 50 / 52 ±2              | 20 / 20                       | 400              | 2 HU, 430 mm                       | 14           |
| BSA 0110-125   | 9 kHz ... 100 MHz | 125 / 150                            | 51 / 53 ±2              | 20 / 20                       | 500              | 2 HU, 430 mm                       | 14           |
| BSA 0110-150   | 9 kHz ... 100 MHz | 150 / 175                            | 51.8 / 54 ±2            | 20 / 20                       | 530              | 2 HU, 430 mm                       | 15           |
| BSA 0110-200   | 9 kHz ... 100 MHz | 200 / 230                            | 53 / 55 ±2              | 20 / 20                       | 800              | 3 HU, 630 mm                       | 27           |
| BSA 0110-250   | 9 kHz ... 100 MHz | 250 / 300                            | 54 / 56 ±2              | 20 / 20                       | 900              | 3 HU, 630 mm                       | 28           |
| BSA 0110-400   | 9 kHz ... 100 MHz | 400 / 440                            | 56 / 58 ±2              | 20 / 20                       | 1700             | 4 HU, 630 mm                       | 37           |
| BSA 0110-500   | 9 kHz ... 100 MHz | 500 / 600                            | 57 / 59 ±2              | 20 / 18                       | 2100             | 4 HU, 630 mm                       | 37           |
| BSA 0110-600   | 9 kHz ... 100 MHz | 600 / 700                            | 57.8 / 60 ±2            | 20 / 18                       | 2500             | 5 HU, 630 mm                       | 58           |
| BSA 0110-1000  | 9 kHz ... 100 MHz | 1000 / 1200                          | 60 / 62 ±2              | 20 / 18                       | 3100             | 5 HU, 630 mm                       | 60           |
| BSA 0110-1500  | 9 kHz ... 100 MHz | 1500 / 1700                          | 61.8 / 64 ±2            | 20 / 18                       | 10000            | 15 HU, 630 mm                      | 200          |
| BSA 0110-3000  | 9 kHz ... 100 MHz | 3000 / 3300                          | 64.8 / 67 ±2            | 20 / 20                       | 14000            | 24 HU, 800 mm                      | 265          |
| BSA 0110-5000  | 9 kHz ... 100 MHz | 5000 / 5500                          | 67 / 69 ±2              | 20 / 20                       | 30000            | 37 HU, 800 mm (XL)                 | 600          |
| BSA 0110-10000 | 9 kHz ... 100 MHz | 10000 / 11000                        | 70 / 72 ±2              | 20 / 20                       | 55000            | 2x 37 HU, 800 mm (XL)              | 1100         |
| BSA 0110-12000 | 9 kHz ... 100 MHz | 12000 / 13000                        | 70.8 / 73 ±2            | 20 / 20                       | 55000            | 2x 37 HU, 800 mm (XL)              | 1100         |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm