

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 1050-50	100 kHz ... 500 MHz	50 / 70	47 / 49 ±2	20 / 20	600	3 HU, 630 mm	19
BSA 1050-100	100 kHz ... 500 MHz	100 / 120	50 / 52 ±2	20 / 20	700	3 HU, 630 mm	20
BSA 1050-150	100 kHz ... 500 MHz	150 / 180	51.8 / 54 ±2	20 / 18	800	3 HU, 630 mm	20
BSA 1050-300/100	100 kHz ... 500 MHz				2200	4 HU, 630 mm	40
	100 kHz ... 400 MHz	300 / 350	54.8 / 57 ±2	20 / 20			
	400 ... 500 MHz	100 / 150	50 / 52 ±2	20 / 20			
BSA 1050-500/100	100 kHz ... 500 MHz				2500	4 HU, 630 mm	38
	100 kHz ... 250 MHz	500 / 600	57 / 59 ±2	20 / 17			
	250 ... 400 MHz	300 / 350	54.8 / 57 ±2	20 / 20			
	400 ... 500 MHz	100 / 120	50 / 52 ±2	20 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm