

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
TWAL 2640-40	26.5 ... 40 GHz	40 / 60	46 / 52 $\pm$ 6	20 / 20	1200	4 HU, 630 mm	27
TWAL 2640-80	26.5 ... 40 GHz				1800	12 HU, 630 mm	115
	26.5 ... 38 GHz	80 / 100	49 / 55 $\pm$ 6	20 / 20			
	38 ... 40 GHz	70 / 80	48.5 / 55 $\pm$ 6	20 / 20			
TWAL 2640-100L	26.5 ... 40 GHz				1000	6 HU, 800 mm	48
	26.5 ... 37 GHz	120 / 135	50 / 56 $\pm$ 6	20 / 20			
	37 ... 40 GHz	100 / 120	50 / 56 $\pm$ 6	20 / 20			
TWAL 2640-120	26.5 ... 40 GHz	120 / 150	50.8 / 57 $\pm$ 6	20 / 20	750	6 HU, 630 mm	38
TWAL 2640-200	26.5 ... 40 GHz	200 / 220	53 / 59 $\pm$ 6	20 / 20	1500	15 HU, 630 mm	115

For individual data sheets, please click on the above model name

1 HU = 44.45 mm