

STANDARD MODELS

| Model | Frequency Range | Output Power P_N min / typ W | Gain min / typ dB | Harmonics 2nd / 3rd dBc | Line Power VA | Dimensions (H, D) 19"-System | Weight kg |
|----------------|-----------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BLWA 1050-100 | 100 ... 500 MHz | 100 / 120 | 50 / 52 ±2 | 20 / 12 | 400 | 3 HU, 430 mm | 19 |
| BLWA 1050-150 | 100 ... 500 MHz | 150 / 180 | 51.8 / 54 ±2 | 20 / 20 | 800 | 3 HU, 430 mm | 24 |
| BLWA 1050-250 | 100 ... 500 MHz | 250 / 300 | 54 / 56 ±2 | 20 / 20 | 1500 | 3 HU, 630 mm | 35 |
| BLWA 1050-500 | 100 ... 500 MHz | 500 / 600 | 57 / 59 ±2 | 20 / 20 | 3000 | 4 HU, 630 mm | 44 |
| BLWA 1050-750 | 100 ... 500 MHz | 750 / 900 | 58.8 / 61 ±2 | 20 / 20 | 4500 | 8 HU, 630 mm | 80 |
| BLWA 1050-1000 | 100 ... 500 MHz | 1000 / 1150 | 60 / 62 ±2 | 20 / 20 | 6500 | 9 HU, 630 mm | 95 |
| BLWA 1050-1500 | 100 ... 500 MHz | 1500 / 1700 | 61.8 / 64 ±2 | 20 / 20 | 10000 | 21 HU, 800 mm | 200 |
| BLWA 1050-2000 | 100 ... 500 MHz | 2000 / 2200 | 63 / 65 ±2 | 20 / 20 | 17000 | 41 HU, 800 mm | 300 |
| BLWA 1050-2500 | 100 ... 500 MHz | 2500 / 2700 | 64 / 66 ±2 | 20 / 20 | 20000 | 41 HU, 800 mm | 400 |
| BLWA 1050-4000 | 100 ... 500 MHz | 4000 / 4400 | 66 / 68 ±2 | 20 / 20 | 35000 | 2x 37 HU, 800 mm | 600 |
| BLWA 1050-5000 | 100 ... 500 MHz | 5000 / 5500 | 67 / 69 ±2 | 20 / 20 | 45000 | 2x 37 HU, 800 mm | 800 |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm